

VENTURE 3®

TRANSPORTING VENTURE II TO THE NEXT LEVEL



PART

ESB5710D***

ESB5710DT*****

ESB5720D***

ESB5720DT*****

ESB5730D*****

LENS

Clear

Clear (Anti-Fog)

Gray

Gray (Anti-Fog)

Amber

PART

ESB5760D***

ESB5770D*****

ESB5780D*****

LENS

Infinity Blue

Silver Mirror

Indoor/Outdoor Mirror

- Soft and adjustable nose piece is ventilated.
- High quality optics offer extreme clarity and no distortion.
- Top of frame is ventilated allowing air to circulate and prevent fogging.
- Perfectly balanced from temple tips to the bridge of the nose, providing the best fit possible.
- Ventilated nose piece is soft and adjustable, allowing heat to dissipate from nose bridge and reduce fogging.
- Soft dual-injected rubber temple tips combined with fully adjustable straight back temples reinforce the highest level of comfort and fit.
- 9.5 base curve lens provides excellent side protection against wind and airborne particles, provides 99% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 12.8mm

Closest Point Between Lens: 13.1mm

Closest Point Between Strap Temple Tips: 91mm

Lens Base: 9.50 Curve

Lens Size Diagonal: 82mm

Lens Size Vertical: 46.6mm

Lens Thickness: 2.3mm

Overall Length (Lens-Tip): 150-163mm

Overall Width (Hinge-Hinge): 139.4mm

PD: 68mm









Weight: 28gm

VENTURE 3®

TRANSPORTING VENTURE II TO THE NEXT LEVEL

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection
Frame	Polycarbonate	Lens clip in frame - Vented at top for air circulation - helps prevent fogging (8 slots)
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Bridge- Polycarbonate	Integral to lens
	Nose Pad - PVC	Pillow softness
Sleeve	Polycarbonate	4 length position adjustment
Temple Tips	Polycarbonate + TPE	Length adjustable with additional co-injected soft cushion tips.
Hinge	Polycarbonate	3 barrel type
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB5710D	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB5710DT	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB5720D	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB5720DT	 Gray (Anti-Fog)	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB5730D	 Amber	2 - 1.2 P 1 F CE	CE P EN166 F
ESB5760D	 Infinity Blue	2C - 1.4 P 1 F CE	CE P EN166 F
ESB5770D	 Silver Mirror	5 - 2.5 P 1 F CE	CE P EN166 F
ESB5780D	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust